

MATERIAL SAFETY DATA SHEET

SECTION ONE - GENERAL INFORMATION Date Revised : 11/10/2009

PRIMARY TRADE NAME:

Unbelievable!® Citrus Gel™ Pro-UCG

GENERIC DESCRIPTION:

Grease, Tar and Adhesive Remover

MANUFACTURER'S NAME AND ADDRESS:

CORE PRODUCTS CO., INC.

401 INDUSTRIAL DR.

CANTON, TX 75103

**HEALTH - 1
FLAMMIBILITY - 0
REACTIVITY - 0
SPECIAL - 0**

EMERGENCY TELEPHONE NUMBER: **Chemtrec 1-800-424-9300**

TELEPHONE NUMBER FOR INFORMATION: **1-800-825-2673**

SECTION TWO - HAZARDOUS INGREDIENTS/HEALTH HAZARD DATA

This product has not been tested as a whole for health effects on animals or humans. This product HAS been tested as a whole for flammability and combustibility and is COMBUSTIBLE as a whole as defined in 29 CFR 1910.1200.

<u>INGREDIENTS:</u>	<u>%</u>	<u>CAS#</u>	<u>OSHA/PEL</u>	<u>ACGIH/TLV</u>
Propylene Glycol Monobutyl Ether	<8	5131-66-8	400 ppm	400 ppm
Ethylene Glycol Monobutyl Ether	<5	111-76-2	25 ppm	25 ppm (skin)
IPA	<2	71-23-8	500 ppm	500 ppm

SECTION THREE - PHYSICAL DATA

BOILING POINT (F): Over 300 F

pH: NA

VAPOR PRESSURE (mm/Hg): ND

SP. GRAVITY (WATER=1) 0.8

VAPOR DENSITY (AIR=1): ND

SOLUBILITY IN WATER: Miscible

EVAPORATION RATE (ETHYL ETHER=1) <1

APPEARANCE AND ODOR: White viscous creamy liquid with citrus odor

SECTION FOUR - FIRE & EXPLOSION HAZARD DATA

FLASH POINT (METHOD):

AUTONITON TEMPERATURE:

LEL:

UEL:

145 ° F PMCC

ND

1.1 % xol

3.4%

EXTINGUISHING MEDIA:

Use normal firefighting procedures, water fog or fine spray, dry chemical, carbon dioxide, or chemical foam.

SPECIAL FIRE FIGHTING PROCEDURES:

As in any fire involving chemicals, wear a self-contained breathing apparatus in pressure-demand, MSHA/NIOSH (approved or equivalent), and full protective gear. High concentrations of vapor or mist at elevated temperatures such as in a fire are irritating to the eyes and respiratory tract and may cause headaches, dizziness, anesthesia, drowsiness, and unconsciousness.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustible liquid.

High concentrations of vapor can travel distances to ignition source and flash back. When exposed to fire carbon dioxide and carbon monoxide may form when heated to decomposition.

SECTION FIVE - HEALTH HAZARD DATA

CARCINOGENICITY: NTP: No IARC: No OSHA: No

PRIMARY ROUTE OF ENTRY: Eyes, Skin, Inhalation and Ingestion

SYMPTOMS OF HEAVY ACUTE AND/OR PROLONGED EXPOSURE

Product contact with eyes will cause irritation. Prolonged or repeated exposure will irritate the skin. Harmful if chronically inhaled. Harmful or Fatal if swallowed due to possible aspiration of material into lungs by ingestion or vomiting which can cause mild to severe pulmonary injury.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Preexisting contact-site disorders. Skin sensitivity, such as dermatitis and/or respiratory disorders

EMERGENCY FIRST AID:

EYES: Flush with plenty of water while lifting eyelids for 15 minutes. If irritation persists, call a physician.

SKIN: Wash with water for 15 minutes. If irritation occurs, seek medical attention.

INGESTION: Do not induce vomiting; get immediate medical attention.

INHALATION: Remove to fresh air, if problem breathing, seek medical attention.

SECTION SIX - REACTIVITY DATA

STABILITY: Stable.

CONDITIONS TO AVOID: None

INCOMPATIBLE MATERIALS TO AVOID: Acids And Oxidizers.

HAZARDOUS POLYMERIZATION: Will not occur.

CONDITIONS TO AVOID: None

HAZARDOUS DECOMPOSITION: Carbon dioxide and carbon monoxide may form when heated to decomposition.

SECTION SEVEN - ENVIRONMENTAL PROTECTION PROCEDURES

SPILL RESPONSE: Wear suitable protective equipment. Eliminate any ignition sources. Contain release by using an inert material such as sand or oil absorbent and/or eliminate the spill source, if this can be done without risk. Take up and containerize for proper disposal. Do not discharge into sanitary sewer or storm sewer. Comply with all federal, state and local regulations on reporting releases.

WASTE DISPOSAL METHOD: Dispose of in accordance with all Local, State, and Federal regulations.

SECTION EIGHT - SPECIAL PROTECTION INFORMATION

EYE PROTECTION: ANSI-approved eyewear

SKIN PROTECTION: Rubber or vinyl gloves.

RESPIRATORY PROTECTION: Not normally required under normal use.

NOTE: When local or mechanical exhaust are not adequate, concentrations of product in air may exceed the limits in Section II, 1200 mg/m³ (152 ppm). Then NIOSH approved respirators would be recommended to prevent overexposure by inhalation.

VENTILATION RECOMMENDATION: Local Exhaust: Recommended

Mechanical: Not normally required other:

OTHER PROTECTION: Long pants and sleeves. Consider an apron.

SECTION NINE - SPECIAL PRECAUTIONS

HANDLING AND STORAGE: Store in cool dry area. Do not store near open flame or electrical sparks. Possible Electrostatic Accumulation Hazard, use proper bonding and/or grounding procedures.

OTHER PRECAUTION: None.

SECTION TEN - TRANSPORTATION INFORMATION:

Exemptions found in 49 CFR 173 may be applied to actual shipments: below is for reference purpose only:

DOT SHIPPING NAME:

DOT HAZARD CLASS:

Compounds, Cleaning Liquid

Not regulated in non-bulk shipments.

UN/NA IDENTIFICATION NUMBER:

DOT LABEL:

UN 1268 PG 111

Non-regulated except bulk shipments.

ENVIRONMENTAL NOTES:

Sara 313-reportable ingredients are not present. Contains traces of ethylene oxide. Reportable under California Prop. 65.

DISCLAIMER OF LIABILITY

The manufacturer and seller warrants that the product conforms to its standard specifications when used according to directions. As the conditions or methods of use are beyond our control, we do not assume any responsibility and expressly disclaim any liability for use of this product. Information contained hereinafter is believed to be true and accurate but all statements or suggestions are made without any warranty, expressed or implied, regarding accuracy of the information, the hazards connected with the use of the material and the results to be obtained from the use thereof.

Footnotes:

NA-Not applicable

NE-data not established

CS-Cancer Suspect Agent

OX-Oxidizer

ND-No data

Cor-Corrosive

CALC-Calculated

EST-Estimated

STEL-Short Time Exposure Limit

TLV-Threshold limit Value

PEL-Permissible Exposure Limit

TWA-Time Weighted Average, 8 hours

HMIS, PPI-Hazardous Material Identification System, Personal Protection Index